

Stainless Services & Solutions
FLAT BARS AND SLIT COILS

For more than 25 years, Aperam Stainless Services & Solutions Luxembourg has specialised in producing and distributing stainless HRAP products from 2 mm to 20 mm thickness, available as flat bars and narrow strips. Thanks to a wide range of grades, dimensions, finishing equipment, polishing and machined edges, we are well-positioned to satisfy all of our customers' needs. Our team would be pleased to demonstrate our commitment to provide industry-leading customer service, on-time delivery and quality products.

- > Market leader
- > Strategic positioning
- > Global deliveries

#### Flat bars

**Length:** from 2 000 to 6 000 mm. Other lengths possible: (below 2 000 mm and up to 8 000 mm) upon request.

**Norms:** EN 10088-2, EN 10028-7, EN 10058, ISO 18286, EN 10088-4 with certificate 3.1 (EN 10204).

**Standard grades:** HRAP 1.4301, 1.4307, 1.4541, 1.4404, 1.4571 (and even more for your project: 1.4003, 1.4016, 1.4509, 1.4512).

Package: bundle of 500 kg.

Service ++: your flat bars with 4 polished sides!

Thickness	Width (mm)		Length (mm)	
(mm)	Mini	Maxi	Mini	Maxi
2	10	120	2 000	6 0 0 0
З	10	300	2 000	6 0 0 0
4	10	300	2 000	6 0 0 0
5	15	250	2 000	6 0 0 0
6	15	300	2 000	6 0 0 0
8	20	300	2 000	6 0 0 0
10	20	300	2 000	6 0 0 0
12	30	300	2 000	6 0 0 0
15	40	250	2 000	6 0 0 0
20	50	250	2 000	4 000-6 000*

\* 6.000 mm for 1.4307 and 4 000 mm for other grades

## Service Centre

Thanks to our state-of-the-art production equipment, we are able to quickly and easily deliver small quantity orders (from 500 kg) on short lead times (within 10 days). We supply a wide-range of top quality stainless steel, enabling us to meet all your demands - from supplying sampling for new projects to unforeseen last minute orders. We keep a constant supply of the most popular grades and thicknesses, which means we can supply within 2 weeks. In addition, we produce surplus material from production on a daily basis, so do not hesitate to contact us to check what is available in stock.

## Our sales team is at your disposal

E: commercial-rodange@aperam.com T: +352 50 54 81 1 GPS: N 49.55433 / E 5.85228

#### Slit coils

**Norms:** EN 10088-2, EN 10028-7, EN 10088-4, ISO 9444-2 (thickness tolerance 1D) & ISO 9445 (thickness tolerance 2B) with certificate 3.1 (EN 10204).

**Standard grades:** HRAP 1.4301, 1.4301 DDQ, 1.4306, 1.4307, 1.4541, 1.4404, 1.4571 (and even more for your project: 1.4003, 1.4016, 1.4509, 1.4512, 1.4462). CRAP upon request.

**Package:** max. 5 tons on pallet (eye to sky), no interleaving paper, wooden spacer 40/80 mm.

**ID:** 508 mm / **OD:** 1000/1850 mm.

Service ++: slit coils available with machined edges.

Thicknocc (mm)	Width (mm)		
Thickness (mm)	Mini	Maxi	
2	10	1 500	
З	10	1 500	
4	10	1 500	
5	15	1 500	
6	15	1 500	
8	20	1 500	
10	20	1 500	
12 to 13	30	1 500	

# Contact